

PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36, and Rule 70)

REC'D 09 JAN 2006

WIPO

PCT

Applicant's or agent's file reference WJ504629-142	FOR FURTHER ACTION		See Form PCT/IPEA/416
International application No. PCT/NZ2004/000274	International filing date (day/month/year) 29 October 2004	Priority date (day/month/year) 31 October 2003	
International Patent Classification (IPC) or national classification and IPC Int. Cl. H04B 5/00 (2006.01) H02M 5/458 (2006.01)			
Applicant AUCKLAND UNISERVICES LIMITED et al			

1. This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.	
2. This REPORT consists of a total of 4 sheets, including this cover sheet.	
3. This report is also accompanied by ANNEXES, comprising:	
a. <input checked="" type="checkbox"/> (sent to the applicant and to the International Bureau) a total of 17 sheets, as follows:	
<input type="checkbox"/> sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).	
<input type="checkbox"/> sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.	
b. <input type="checkbox"/> (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)) , containing a sequence listing and/or table related thereto, in electronic form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).	
4. This report contains indications relating to the following items:	
<input checked="" type="checkbox"/> Box No. I	Basis of the report
<input type="checkbox"/> Box No. II	Priority
<input type="checkbox"/> Box No. III	Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
<input checked="" type="checkbox"/> Box No. IV	Lack of unity of invention
<input checked="" type="checkbox"/> Box No. V	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
<input type="checkbox"/> Box No. VI	Certain documents cited
<input type="checkbox"/> Box No. VII	Certain defects in the international application
<input type="checkbox"/> Box No. VIII	Certain observations on the international application

Date of submission of the demand 30 May 2005	Date of completion of this report 01 January 2006
Name and mailing address of the IPEA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustalia.gov.au Facsimile No. (02) 6285 3929	Authorized Officer James Williams Telephone No. (02) 6283 2599

Box No. I Basis of the report

1. With regard to the language, this report is based on:
- ☒ The international application in the language in which it was filed
- ☐ A translation of the international application into _____, which is the language of a translation furnished for the purposes of:
- ☐ international search (under Rules 12.3(a) and 23.1 (b))
- ☐ publication of the international application (under Rule 12.4(a))
- ☐ international preliminary examination (Rules 55.2(a) and/or 55.3(a))
2. With regard to the elements of the international application, this report is based on (*replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report*):
- ☐ the international application as originally filed/furnished
- ☒ the description:
- pages 1-2 as originally filed/furnished
- pages* 3-13 received by this Authority on 29 August 2005 with the letter of the same
- pages* received by this Authority on with the letter of
- ☒ the claims:
- pages as originally filed/furnished
- pages* as amended (together with any statement) under Article 19
- pages* 14-19 received by this Authority on 29 August 2005 with the letter of the same
- pages* received by this Authority on with the letter of
- ☒ the drawings:
- pages 1-15 as originally filed/furnished
- pages* received by this Authority on with the letter of
- pages* received by this Authority on with the letter of
- ☐ a sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing.
3. ☐ The amendments have resulted in the cancellation of:
- ☐ the description, pages
- ☐ the claims, Nos.
- ☐ the drawings, sheets/figs
- ☐ the sequence listing (*specify*):
- ☐ any table(s) related to the sequence listing (*specify*):
4. ☐ This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).
- ☐ the description, pages
- ☐ the claims, Nos.
- ☐ the drawings, sheets/figs
- ☐ the sequence listing (*specify*):
- ☐ any table(s) related to the sequence listing (*specify*):

If item 4 applies, some or all of those sheets may be marked "superseded."

Box No. IV Lack of unity of invention

1. ☐ In response to the invitation to restrict or pay additional fees the applicant has, within the applicable time limit:
- ☐ restricted the claims
 - ☐ paid additional fees
 - ☐ paid additional fees under protest and, where applicable, the protest fee
 - ☐ paid additional fees under protest but the applicable protest fee was not paid
 - ☐ neither restricted the claims nor paid additional fees
2. ☒ This Authority found that the requirement of unity of invention is not complied with and chose, according to Rule 68.1, not to invite the applicant to restrict or pay additional fees.
3. This Authority considers that the requirement of unity of invention in accordance with Rules 13.1, 13.2 and 13.3 is:
- ☐ complied with.
- ☒ not complied with for the following reasons:
- The claims do not relate to one invention only (or to a group of inventions so linked as to form a single general inventive concept). In assessing whether there is more than one invention claimed, I have given consideration to those features which can be considered to be "special technical features". These are features that potentially distinguish the claimed combination of features from the prior art. Where different claims have different special technical features they define different inventions. I have found claims having different special technical features as follows:
- (1) Claims 1-18. It is considered that capacitive coupling of the near field antenna comprises a first special technical feature.
 - (2) Claims 19-40. It is considered that the shielding of the near field antenna comprises a second special technical feature.
4. Consequently, this report has been established in respect of the following parts of the international application:
- ☒ all parts.
- ☐ the parts relating to claims Nos.

Box No. V	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement		
1. Statement			
	Novelty (N)	Claims 1-41	YES
		Claims	NO
	Inventive step (IS)	Claims 1-41	YES
		Claims	NO
	Industrial applicability (IA)	Claims 1-41	YES
		Claims	NO
2. Citations and explanations (Rule 70.7)			
	Novelty and Inventive Step		
	D1: US 5,084,864		
	D2: US 5,293,308		
	D3: US 4,636,771		
	D1 discloses a broadband inductively coupled duplex RF transmission system with a balanced transmission line on which a central unit can communicate with a number of remote units each of which are inductively coupled with the transmission line and include RF receivers and transmitters. The units are coupled through a U-shaped coupler to the transmission line. This U-shaped coupler is in effect a near field antenna. The transmission line is terminated in the characteristic impedance.		
	D2 discloses an inductive power distribution system with the features of the HID/IPT section of Claim 20.		
	D3 discloses a power line communications terminal and interface circuit with a transmitter and a receiver. D2 does not disclose a near field antenna.		
	None of the citations individually or in combination disclose all of the features of the claimed invention in particular they do not disclose capacitive coupling or shielding of the near field antenna.		

cable runs alongside the primary power cable of an HID/IPT system. The conductors of the data cable are arranged in such a way as to keep coupling between the data cable and the power cable to a minimum, and therefore reduce "crosstalk". The frequency of the information signal in the data cable is typically less than 1 Megahertz and the transmission rate is about 10 to 150 kbit/s. This system requires a very specific geometric relationship between the data cable and the power cable.

Summary of Invention

It is an object of the present invention to provide communication apparatus or methods which overcome or ameliorate one or more disadvantages of known communication systems. Alternatively it is an object of the invention to at least provide the public with a useful alternative.

Accordingly in one aspect the invention consists in communication apparatus comprising: a communication path capable of conveying communication signals, a communication device adapted to receive or generate VHF or UHF communication signals, and a near field antenna associated with the communication device, the near field antenna being capacitively coupled to the communication path to couple VHF or UHF communication signals to or from the communication device to the communication path.

The near field antenna is preferably adapted to limit electromagnetic radiation therefrom.

The near field antenna may include elongate conductors provided on a non-conductive planar substrate.

The communication path most preferably comprises a transmission line in the form of a cable having two parallel conductors. The conductors may be separated by an insulating web.

The communication device is preferably moveable along the communication path and the near field antenna moves with the communication device and relative to the communication path to allow the communication device to receive or generate VHF or UHF communication signals to or from the communication path.

In a second aspect the invention consists in an HID/IPT system including:

a power supply path adapted to be energised by a power supply to provide an electromagnetic field associated with the power supply path;

one or more moveable pick-up devices associated with the power supply path and adapted to receive electrical energy from the electromagnetic field to supply a load;

a communication path capable of conveying communication signals,

a communication device provided on each of the one or more pick-ups, the communication device being adapted to receive or generate VHF or UHF communication signals; and

a coupling means associated with the communication device, the coupling means being capacitively coupled to the communication path to couple VHF or UHF communication signals to or from the communication device to the communication path whereby the one or more pick-ups may communicate with each other or with a further device.

The further device may interface with a control system and may be directly connected to the communication path.

The coupling means preferably comprises a near field antenna.

In a third aspect the invention consists in a communication method, the method including the steps of:

providing a communication path capable of conveying communication signals;

providing a communication device, the communication device including a near field antenna capacitively coupled to the communication path, and either;

a) imposing a VHF or UHF communication signal on the communication path and using the near field antenna to provide the signal to the communication device, or

b) using the communication device to generate a VHF or UHF communication signal and using the near field antenna to provide the signal to the communication path.

In a fourth aspect the invention consists in a near field antenna comprising a thin planar substrate of a non-conductive material, a conductive track on one side of the substrate adapted to inductively or capacitively couple with a transmission line, and a screen provided on the other side of the substrate.

In a fifth aspect the invention consists in a communication system comprising:

a communication path capable of conveying communication signals,

a communication device adapted to receive or generate VHF or UHF communication signals, and

a near field antenna associated with the communication device, the near field antenna being provided sufficiently near to the communication path to couple VHF or UHF communication signals to or from the communication device to the communication path, the near field antenna including a shielding means to limit electromagnetic radiation.

The near field antenna may comprise a partial, single or multiple turn of a conductive material. The conductive material may be a thin metal track provided on a non-conductive planar substrate.

In a preferred embodiment the conductive material comprises one or more turns being approximately 5mm to 15mm in a lateral dimension and approximately 20mm to 60mm in a longitudinal dimension.

A shielding means may be provided to limit electromagnetic radiation. The shielding means preferably comprises a screen, and the screen is provided on one side of the coupling means and the communication path is provided on an opposite side of the coupling means.

The screen may be constructed of an electrically conductive material having a low magnetic permeability, and be provided on a side of the planar substrate opposite to a side of the substrate on which the metal track is provided.

In a sixth aspect the invention consists in An HID/IPT system including:

a power supply path adapted to be energised by a power supply to provide an electromagnetic field associated with the power supply path;

one or more moveable pick-up devices associated with the power supply path and adapted to receive electrical energy from the electromagnetic field to supply a load;

a communication path capable of conveying communication signals,

a communication device provided on each of the one or more pick-ups, the

communication device being adapted to receive or generate VHF or UHF communication signals; and

a coupling means associated with the communication device, the coupling means being

provided sufficiently near to the communication path to couple VHF or UHF communication signals to or from the communication device to the communication path whereby the one or more pick-ups may communicate with each other or with a further device, the coupling means including a shielding means to limit electromagnetic radiation.

5

Further aspects of the invention, which should be considered in all its novel aspects, will become apparent to those skilled in the art upon reading the following description which provides at least one example of a practical application of the invention.

10

Drawing Description

One or more examples of applications of the invention will be described below with reference to the accompanying drawings in which:

15

Figure 1 is a diagrammatic illustration of a known HID/IPT system,

Figure 2 is a diagrammatic illustration of a communication system according to the invention,

Figure 3 is a diagrammatic illustration of another embodiment of a communication system according to the invention,

20

Figure 4 is a sketch of a near field antenna,

Figure 5 is a partial elevation of a cable used in accordance with the invention,

Figure 6 is an end elevation of the cable of Figure 5,

Figure 7 is a diagrammatic elevation of the inductor of Figure 4 in use relative to the cable of Figures 5 and 6,

25

Figure 8 is an end elevation of the arrangement shown in Figure 7, and

Figure 9 is an end elevation in cross section showing the orientation of the communication path and antenna relative to the power conductors in an example of an HID/IPT application,

30

Figure 10 is an end elevation in cross section of an alternative arrangement of a communication path and a near field antenna in an HID/IPT application,

Figure 11 is a plan view from below of the near field antenna of Figure 10,

Figure 12 is a partial view of the near field antenna and communication path of Figure 10, showing the arrangement in greater detail,

35

Figure 13 is a graph of insertion loss against distance between a near field antenna as shown and described with reference to Figures 10 to 12 and a communication path comprising a 300-Ohm ribbon,

Figure 14 is a diagrammatic end elevation in cross section of a capacitive near field antenna near a parallel conductor transmission line,

Figure 15 is a partial plan view of the near field antenna shown in Figure 14.

5 Detailed Description

An example of the invention will be discussed below with reference to use in an HID/IPT system. However, the invention is applicable to communications systems for many other applications.

10

15

20

Referring to Figure 1 a known HID/IPT system is shown. Such a system is described in US patent 5,293,308, the contents of which are included by reference herein in their entirety. The system includes a conductive path 1 that is electrically energised by a power supply 2. The path 1 may include compensation capacitors 3. A device 4 is supplied with power from the path 1 by being selectively coupled to the path. Thus the device 4 has a tuned power pick-up circuit 5, rectifier bridge 6 and control components as described in US 5,293,308 to provide power as required by a load. The load supplied will vary upon the application of the system, and may for example be a light, or an electric motor. In many applications the path 1 will be provided along a rail or track on which bodies such as carriages are provided, and the load will include an electric motor which moves the carriage along the track.

25

As discussed above, communication with or between devices 4 is important to the operation and efficiency of such systems. For example, if the carriages are used to move articles through a manufacturing process area, it is important to know where each carriage is to avoid collisions or to correctly synchronise the manufacturing process. Communication can be used to allow each carriage to report its position, or to perform certain tasks.

30

35

The present invention provides a communication system where IPT concepts may be applied to allow communication between devices. Referring to Figure 2, an example of the communication system is shown having a communication path 10. Characteristically a suitable communication path is a transmission line that in principle does not radiate energy. It is preferably terminated with its characteristic impedance to avoid standing waves. A communication device 12 may transmit or receive (or both) VHF and/or UHF signals in the form of electrical energy to or from the path 10. For the purposes of this

document the VHF band is 30 MHz to 300 MHz and the UHF band is 300 MHz to 3000 MHz. The device 12 includes, or is associated with, a near field antenna 11.

Communication signals propagating in the communication path are in principle not disturbed by extraneous electromagnetic radiation, as parallel wire transmission lines neither radiate nor receive radiation. Thus the pathway is resistant to unwanted noise. However, near field disturbances can be coupled into or out of the path using near field antennas 11. These are essentially mutual inductances or capacitances that affect the two wires of the communication path differently. In Figure 2 the near field antennas 11 are essentially inductors having inductance L which is coupled to path 10 by mutual inductance M. In this document reference to "near field antenna" refers to an antenna designed to operate in the very near field, preferably within approximately $1/6^{\text{th}}$ of a wavelength or 1 radian phase displacement.

In Figure 2 a communication signal transmitter and/or receiver 14 (a 50-Ohm device in this example) is directly coupled to the path 10 which comprises a transmission line having a 300-Ohm characteristic impedance (such as 300-Ohm television ribbon) via a matching transformer 16. The path is terminated with its characteristic impedance, which in this example comprises a 300-Ohm resistor 18. The communication unit 14 may interface with a controller to communicate instructions to a device associated with communication unit 12.

An alternative arrangement (using like reference numerals to designate like features) is shown in Figure 3. The path 10 in this example is terminated at both ends with resistors 18 corresponding to the characteristic impedance of the cable that provides path 10, and two communication units are coupled to the path so that the path allows communication signals to be transmitted and/or received between the units 12.

Conventional 2-wire transmission lines, such as the 300 - Ohm ribbon cable described above are effective at propagating VHF and UHF signals with very little loss of signal over large distances, for example 100 metres or so. Such ribbon looks like a HID/IPT track and we have found that near-field antennas 11 can be used to insert or extract signals from the 300-Ohm ribbon. The near field antennas 11 are in the preferred form small mutual inductances that couple inductance L to the path 10. However, a near field antenna that is in effect primarily capacitive (that is to say is operative by primarily producing an electric field rather than a magnetic field) could alternatively be used (as shown in Figures 14 and 15). The mutually coupled near-field antennas are designed to be physically small, so

that they themselves do not radiate. In practice this condition is easily met, and practical implementation of the near field antenna is discussed further below. The mutual inductance so formed is small, being of the order of 10 nH. However, at these frequencies (for example 320 MHz in a preferred embodiment) the radian frequency ($2\pi f$) is high (in the order of 2×10^9) so that the product ωM is a quite reasonable value (in this example 20 Ohms).

We have found that a 300-Ohm ribbon HID/IPT system with near field antennas behaves in a very similar manner to a 10-20kHz HID/IPT system. However there are also significant differences. In both systems power is introduced at one end of the cable and may be extracted by pick-ups placed or moving along the track. The conventional track is terminated by a short circuit and at regular intervals along a (long) track compensation capacitors must be placed to prevent the driving voltage from becoming too high. The 300-Ohm ribbon cable is terminated in its characteristic impedance so no compensation capacitors are required. It is not practical to terminate the conventional HID/IPT system in its characteristic impedance as the power losses would be too high. For example, for a track with a track current of 80 A and a characteristic impedance of 180 Ohms the losses in a terminating resistor would be 1.15MW and the operating voltage would be 14.4kV. These differences apart, we have found that the two systems behave almost identically. The communication units 12 and their antennas 11 used with the 300-Ohm ribbon cable are very simple AC (RF) devices and are fully reversible. The near field antennas are designed to repel flux rather than attract it and do not require decoupling from the communication path as they do not have to be tuned and they place very little load on the track. Their reversibility is an advantage.

One embodiment of a communications system is described below with reference to Figures 4 to 9. Referring to those Figures, an antenna for use with a 300-Ohm ribbon cable is a small single turn inductor (although those skilled in the art will realise that other physical arrangements may be used such as a partial turn or more than one turn) with a shape that is preferably rectangular as shown in Figure 4. In that Figure, the longitudinal side 20 of the rectangular shape may be 20 mm to 60 mm (preferably 40 mm) for example, and the lateral (shorter) side 22 may be 5 mm to 15 mm (preferably 8 mm to match the width of the 300-Ohm ribbon) for example. The inductor may be formed using a printed circuit board (PCB) so that the majority of the conductive surface of the original board is etched away to leave the generally rectangular conductive strip. The inductor so formed is connected to the communication device 12, for example by a coaxial cable 24.

Turning to Figures 5 and 6, a portion of ribbon cable is shown, generally referenced 30, having two conductors 32 that are spaced approximately 8 mm apart being separated by an insulating web 34.

5

In Figures 7 and 8 the typical disposition of the antenna 11 relative to the ribbon cable is shown. A side 20 of the inductor L is placed parallel to, and in close proximity with (for example within 5mm to 10mm of) one of the conductors 32 of the ribbon. The antenna 11 and the ribbon are preferably in the same plane in this example. This antenna has a self-inductance of around 40nH and a mutual inductance to the track of approximately 10 nH. If the antenna path 10 is truly in the near-field of the antenna then simple circuit theory may be used to calculate its performance. With the dimensions given as above and with a path comprising a 300-Ohm ribbon terminated in 300 Ohms at both ends, the calculated loss from one antenna driven by a 50 Ohm generator to another antenna is 49.5 dB; the measured loss in the same circumstances is 51 dB. Similarly if the ribbon is driven with a matching transformer to match 300 Ohms to a 50 Ohm generator the calculated loss from the generator to the antenna is 28 dB against a measured loss of 31 dB. For propagation in the opposite direction from the pick-up to the generator the figures are again 28 dB and 31 dB.

20

In Figure 9 a diagrammatic cross section is shown through a rail assembly 40 of an IPT system installation. The rail supports the track or primary power conductors 42 which are arranged to allow passage of a power pick-up core 44. The communication conductor 10 (comprising ribbon 30) is shown provided on the rail assembly, and the antenna 11 is shown in close proximity to the ribbon, being supported by an arm 46 from the core so as to move with the core if necessary.

25

In an HID/IPT system the effect of a loaded antenna is to reflect an impedance back into the track. Thus a 3 kW load reflects a resistance of 0.469 Ohms back into a track with 80 A in it to produce the 3 kW (assuming no loss). Similarly the 300-Ohm ribbon also has a reflected impedance of approximately 0.7 Ohms induced in it. This is small compared with the characteristic impedance and has very little effect on the propagation of signals in the ribbon. With the ribbon an antenna sending power to the ribbon also sees a back-reflected impedance (again of 0.7 Ohms). This is small and even though it is a mismatch it has very little effect on the performance of the antenna or the ribbon.

30

35

Referring now to Figures 10 to 12, another embodiment will be described. In Figures 10 to 12, features that are the same as, or similar to, those of preceding Figures have the same reference numerals.

5 In Figure 10, the ribbon 30 is shown provided on an alternative rail assembly 50 of an IPT system installation. For purposes of clarity, the primary power conductors are not shown, but are supported from structure 52 (which may comprise an "I" beam for example). The antenna 11 is provided in a plane substantially parallel to but above that of the ribbon 30.

10 Referring to Figure 11, one side of the near field antenna 11 is shown in greater detail. As described above, the near field antenna may be constructed in a number of different ways, but is preferably formed from etching a PCB to provide track 54 which in this example forms a two-turn inductor. We have found that the near field antenna may be formed from a double sided printed circuit board to create two turns of narrow (preferably
15 1 mm) wide copper track about 1 mm apart on one side, and a copper screen 56 (not shown in Figure 11, but illustrated in Figure 12) on the other side. The screen 56 has a low magnetic permeability and therefore repels magnetic flux, so it acts as a "flux
20 frightener" rather than HID/IPT system power transfer units which try to attract flux using ferrite or similar high permeability materials. We have made these on a double sided PCB laminate 1.6 mm thick (to give 1.6 mm between the loop and the screen behind it) and on two separate single sided laminates that were then glued together to get a thickness of 3.2 mm. Thicker antennas allow greater spacing between the 300 Ohm ribbon and the antenna. The distance from the ribbon to the physical structure (typically aluminium) it is attached to is preferably 1.6 mm for the 1.6 mm thick antennas but for larger separations
25 3-5 mm is preferred with the thicker antennas. The longitudinal dimension 20 is 40 mm in this example, and the lateral dimension 22 is 8 mm. We use a direct connection to a 50 Ohm coax cable with the central conductor going to one terminal 58 and the earth screen to the other terminal 60. We have found that we do not require any matching networks. We have also made antennas 30 mm long (i.e. 30mm in the longitudinal dimension 20).
30 These are slightly less sensitive (-2 to -3 dB). The length and width (i.e. the longitudinal and lateral dimensions respectively) may be changed as required. Increased width may be desirable for a wider ribbon to accommodate the greater spacing between the parallel conductors, or to allow greater spacing between the antenna and the ribbon (since a greater width may allow flux to extend further toward the ribbon). Increased length allows
35 higher gain, although this needs to be kept relatively small (longitudinal dimension) <<

wavelength) to prevent radiation and to communication in locations where the ribbon is bent around corners.

5 The PCB laminate is preferably cropped to extend about 20 mm from the loop in all directions to prevent radiation. Thus the screen 56 extends beyond the dimensions of the track 54. In cases where this is not possible we have found that the laminate may be cropped more closely where needed. The extra screening helps to suppress unwanted radiation. The result is a near field antenna that has very little radiation at the operating frequency of typically 320 MHz. Furthermore, the balanced and properly terminated
10 ribbon 30 also radiates essentially no power.

Turning to Figure 12, the arrangement of Figure 10 is shown in greater detail. The ribbon 30 is spaced from the structure 52 by a spacer 62 (which is preferably constructed from a plastic material such as a plastics tape or web) which is approximately 1.5 mm high in this
15 example. The ribbon may typically extend approximately 1.5 mm above the spacer, and the near field antenna may be provided about 1.5 mm to 5 mm above the ribbon, as discussed above. Therefore, the overall profile may be as low as about 3 mm without the near field antenna, and 6 mm - 7 mm with the near field antenna.

20 The structure 52 will often be aluminium, and we have found that this causes significant signal attenuation, for example up to 0.4 dB per meter. This together with the near field antenna design which is physically small, and may include screen 56 to limit any radiation, substantially prevents any power being radiated, and thus avoids EMI (Electromagnetic Interference) problems. Also, the extreme difference in the HID/IPT operating frequency
25 (around 20 kHz) compared with the communications path operating frequency (around 320 MHz) prevents crosstalk from being an issue.

30 In Figure 13 a graph showing Insertion loss (in dB) against distance (in mm) between the near field antenna described above with reference to Figure 10 to 12 and the 300-Ohm ribbon 30 is shown. As can be seen, the loss increases linearly at 4 dB per mm after 1 mm separation (i.e. from approximately 0.1% of a wavelength).

35 Figures 14 and 15 show an alternative embodiment (using like reference numerals to designate like features) of the near field antenna in which the near field antenna is a capacitive near field antenna 70. The coaxial cable 24 which is connected to a communication device is coupled to the near field antenna 70 by a transformer 72. Each

terminal of the other side of the transformer is connected to one of elongate conductors 74 and 76 which are each near to one of the parallel conductors 32 of the ribbon 30. The plan view in Figure 15 omits the transformer detail and the coaxial cable for clarity. In use an electric field is formed between the near field antenna conductors 74 and 76 and the cable conductors 32, allowing near field disturbances to be coupled into and out of the ribbon 30.

From the foregoing it will be seen that an effective solution is provided to the problem of communications in IPT systems. Those skilled in the art will see that the communication system of the invention may also be used in non-HID/IPT applications, for example applications where vehicles or other bodies are powered by electrical and physical contact with a conductive path. Furthermore, the invention provides a communication system that allows high bandwidth without requiring a physical connection to be made between the communication apparatus. Therefore, the invention can eliminate problems associated with conventional plugs and sockets, and is particularly useful for use with devices that are moveable.

Throughout this document the word "comprise" and variations thereof is intended to be interpreted in an inclusive sense.

Where in the foregoing description reference has been made to specific components or integers of the invention having no equivalents, then such equivalents are herein incorporated as if individually set forth.

Although this invention has been described by way of example and with reference to possible embodiments thereof, it is to be understood that modifications or improvements may be made thereto without departing from the scope of the invention as defined in the appended claims.

Claims:

1. A communication system comprising:
a communication path capable of conveying communication signals,
5 a communication device adapted to receive or generate VHF or UHF communication signals, and
a near field antenna associated with the communication device, the near field antenna being capacitively coupled to the communication path to couple VHF or UHF communication signals to or from the communication device to the communication path.
- 10 2. A communication system as claimed in claim 1 wherein the near field antenna is adapted to limit electromagnetic radiation therefrom.
3. A communication system as claimed in claim 1 or claim 2 wherein the
15 communication path is provided in the very near field of the near field antenna.
4. A communication system as claimed in claim 4 wherein the near field antenna includes elongate conductors provided on a non-conductive planar substrate.
- 20 5. A communication system as claimed in any one of the preceding claims wherein the communication path is a transmission line comprising a cable having two parallel conductors.
6. A communication system as claimed in claim 5 wherein the conductors are
25 separated by an insulating web.
7. A communication system as claimed in claim 5 or claim 6 wherein the cable comprises a ribbon cable.
- 30 8. A communication system as claimed in any one of the preceding claims wherein the communication path is terminated with a resistance corresponding to the characteristic impedance of the path.
9. A communication system as claimed in any one of the preceding claims wherein
35 the system includes a communication device directly coupled to the communication path.

10. A communication system as claimed in any one of the preceding claims wherein essentially no power is radiated from the communication path.

5 11. A communication system as claimed in any one of the preceding claims wherein the system allows bi-directional communication between the communication device the communication path.

10 12. A communication system as claimed in any one of the preceding claims wherein the communication device is moveable along the power supply path and the near field antenna moves with the communication device and relative to the communication path to allow the communication device to receive or generate VHF or UHF communication signals to or from the communication path.

15 13. An HID/IPT system including:
a power supply path adapted to be energised by a power supply to provide an electromagnetic field associated with the power supply path;
one or more moveable pick-up devices associated with the power supply path and adapted to receive electrical energy from the electromagnetic field to supply a load;
a communication path capable of conveying communication signals,
20 a communication device provided on each of the one or more pick-ups, the communication device being adapted to receive or generate VHF or UHF communication signals; and
a coupling means associated with the communication device, the coupling means being capacitively coupled to the communication path to couple VHF or UHF communication
25 signals to or from the communication device to the communication path whereby the one or more pick-ups may communicate with each other or with a further device.

30 14. An HID/IPT system as claimed in claim 13 wherein the further device interfaces with a control system.

15. An HID/IPT system as claimed in claim 13 or claim 14 wherein the further device is directly connected to the communication path.

35 16. An HID/IPT system as claimed in any one of claims 13 to 15 wherein the coupling means comprises a near field antenna.

17. An IPT/HID system as claimed in any one of claims 13 to 16 wherein essentially no power is radiated from the communication path.

18. A communication method including the steps of:

5 providing a communication path capable of conveying communication signals;
providing a communication device, the communication device including a near field antenna capacitively coupled to the communication path, and either,

a) imposing a VHF or UHF communication signal on the communication path and using the near field antenna to provide the signal to the communication device,

10 or

b). using the communication device to generate a VHF or UHF communication signal and using the near field antenna to provide the signal to the communication path.

19. A communication system comprising:

15 a communication path capable of conveying communication signals,

a communication device adapted to receive or generate VHF or UHF communication signals, and

20 a near field antenna associated with the communication device, the near field antenna being provided sufficiently near to the communication path to couple VHF or UHF communication signals to or from the communication device to the communication path, the near field antenna including a shielding means to limit electromagnetic radiation.

20. A communication system as claimed in claim 19 wherein the communication path is provided in the very near field of the near field antenna.

21. A communication system as claimed in claim 19 or claim 20 wherein the near field antenna is inductively coupled to the communication path.

22. A communication system as claimed in any one of claims 19 to 21 wherein the near field antenna comprises a partial, single or multiple turn of a conductive material.

23. A communication system as claimed in claim 22 wherein the conductive material comprises a thin metal track provided on a non-conductive planar substrate.

24. A communication system as claimed in claim 23 wherein the conductive material

comprises one or more turns being approximately 5mm to 15mm in a lateral dimension and approximately 20mm to 60mm in a longitudinal dimension.

25. A communication system as claimed in any one claims 19 to 24 wherein the shielding means comprises a screen, and the screen is provided on one side of the coupling means and the communication path is provided on an opposite side of the coupling means.

26. A communication system as claimed in any one of claims 19 to 25 wherein the shielding means comprises a screen of a material having a low magnetic permeability, and the screen is provided on a side of the planar substrate opposite to a side of the substrate on which the metal track is provided.

27. A communication system as claimed in any one of claims 19 to 26 wherein the communication path is a transmission line comprising a cable having two parallel conductors.

28. A communication system as claimed in claim 27 wherein the conductors are separated by an insulating web.

29. A communication system as claimed in claim 27 or claim 28 wherein the cable comprises a ribbon cable.

30. A communication system as claimed in any one of claims 19 to 29 wherein the communication path is terminated with a resistance corresponding to the characteristic impedance of the path.

31. A communication system as claimed in any one of the claims 19 to 30 wherein the system includes a communication device directly coupled to the communication path.

32. A communication system as claimed in any one of claims 19 to 31 wherein essentially no power is radiated from the communication path.

33. A communication system as claimed in any one of claims 19 to 32 wherein the system allows bi-directional communication between the communication device the communication path.

34. A communication system as claimed in any one of claims 19 to 33 wherein the communication device is moveable along the power supply path and the near field antenna moves with the communication device and relative to the communication path to allow the communication device to receive or generate VHF or UHF communication signals to or from the communication path.

35. An HID/IPT system including:
a power supply path adapted to be energised by a power supply to provide an electromagnetic field associated with the power supply path;
one or more moveable pick-up devices associated with the power supply path and adapted to receive electrical energy from the electromagnetic field to supply a load;
a communication path capable of conveying communication signals,
a communication device provided on each of the one or more pick-ups, the communication device being adapted to receive or generate VHF or UHF communication signals; and
a coupling means associated with the communication device, the coupling means being provided sufficiently near to the communication path to couple VHF or UHF communication signals to or from the communication device to the communication path whereby the one or more pick-ups may communicate with each other or with a further device, the coupling means including a shielding means to limit electromagnetic radiation.

36. An HID/IPT system as claimed in claim 35 wherein the further device interfaces with a control system.

37. An HID/IPT system as claimed in claim 36 or claim 36 wherein the further device is directly connected to the communication path.

38. An HID/IPT system as claimed in any one of claims 35 to 37 wherein the coupling means comprises a near field antenna.

39. A communication system substantially according to any one of the embodiments herein described with reference to Figures 2 to 15 of the accompanying drawings.

40. An HID/IPT system substantially according to any one of the embodiments herein

described with reference to Figures 2 to 15 of the accompanying drawings.

41. A communication method as claimed in claim 18 and substantially as herein described.

5

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.